

Metal ion removal from electrolyte

Patent Number: DE19731616

Publication date: 1999-01-28

Inventor(s): IOURTCHOUK TATIANA DR (DE); BERGMANN HENRY PROF DR (DE)

Applicant(s): IOURTCHOUK TATIANA DR (DE); BERGMANN HENRY PROF DR (DE)

Requested Patent: ☐ DE19731616

Application Number: DE19971031616 19970723

Priority Number(s): DE19971031616 19970723

IPC Classification: C25D21/18; C25B15/08; C23G1/36; C25F7/02; C02F1/461; C02F1/469

EC Classification: C02F1/469, C02F1/467D2, C25D21/18

Equivalents:

Abstract

In a process and cell unit for material removal from an electrolyte, the electrolyte is passed through two electrolysis/electrodialysis units referred to as primary and secondary cells (1, 2). The primary cell (1) consists of an anode (6), a cathode (7) and preferably three sub-cells, separated by two separators (3, 4) to form a central chamber which separates an anode space or anolyte circulation system from a cathode (7) or catholyte circulation system, the electrolyte (11) being passed through the space containing the cathode (7) or connected to the catholyte circulation system. A second electrolyte circulation connection (12) can be produced between the catholyte system of the primary cell and that of the secondary cell (2), the secondary cell comprising an anode (10), a cathode (9), catholyte and anolyte systems and two sub-cells separated by a separator (8).

Data supplied from the esp@cenet database - I2